

VEROTEX CURTAIN TRACK SYSTEM “VEROTEC FMS PLUS”



PRODUCT INFORMATION

- SMOOTH, BELT DRIVEN MOTORIZED CURTAIN TRACK SYSTEM.
- HIGH FREQUENCY TECHNOLOGY.
- CAN BE OPERATED BY WALL SWITCH, REMOTE CONTROL (HIGH FREQUENCY) OR TIME SWITCH (HIGH FREQUENCY)
- SILENT MOTOR, SPEED: 15 CM/SEC.
- EASY TO CONNECT TO BUILDING AUTOMATION SYSTEMS.
- BI-DIRECTIONAL BUS-CONTROLLER AVAILABLE, WHICH ENABLES DATA FEEDBACK COMMUNICATION. OPTIONAL.
- AVAILABLE IN 30, 45 AND 60 WATT;
- DIRECT 230V AC MOTOR WITHOUT ANY TRANSFORMER SYSTEMS. THE MOTOR IS ONLY ON POWER IF THE SWITCH BUTTON WILL BE PRESSED. IMPORTANT FOR FIRE SAFETY.

VEROTEX CURTAIN TRACK SYSTEM “VEROTEC FMS PLUS”

- MOTOR PULLEY CONNECTS MOTOR AND FMS TRACK. ALSO AVAILABLE IN UPSIDE-DOWN VERSION TO HIDE THE MOTOR INTO THE CEILING.
- ALL KS BRACKETS APPLICABLE.

- TORQUE: 0,8 NM (30 WATT), 1.2 NM (45 WATT), 1.6 NM (60 WATT)
-
- DIMENSIONS:
 - 30 WATT MOTOR: 60 X 50 X 200 MM (2.36 X 1.97 X 7.87”)
 -
 - 45 WATT MOTOR: 60 X 50 X 230 MM (2.36 X 1.97 X 9.06”)
 -
 - 60 WATT MOTOR: 60 X 50 X 230 MM (2.36 X 1.97 X 9.06”)
 -
 - RECEIVER BOX: 50 X 85 X 85 MM (1.97 X 3.35 X 3.35 INCH)
 -
- **FMS PLUS® AND RECESS FIXATION**
- INSTEAD OF A REGULAR CEILING FIX OR WALL FIX
INSTALLATION OF THE FMS TRACK SYSTEM, VEROTEX ALSO OFFERS A SOLUTION FOR A RECESS FIXED MOTORIZED CURTAIN TRACK. THE FMS PLUS® SYSTEM IS IDEAL FOR A CLEAN, CONCEALED CURTAIN TRACK INSTALLATION. THE RECESS PROFILE CAN BE FITTED DURING THE CONSTRUCTION OF THE CEILING, THE FMS PLUS® MOTORIZED TRACK CAN THEN BE FITTED ONCE ALL THE FINISHING WORKS HAVE BEEN COMPLETED. THE MOTOR CAN BE PLACED IN A REGULAR POSITION, OR INVERTED INTO THE CEILING. THE SYSTEM CAN

VEROTEX CURTAIN TRACK SYSTEM “VEROTEC FMS PLUS”

BE FITTED WITH REGULAR FMS CARRIERS, ROTATING CARRIERS OR THE FOREST EASY FOLD SYSTEM.

- **MOTOR OPTIONS**
- ALL TYPES OF VEROTEX FMS MOTORS CAN BE USED ON THE FMS PLUS® TRACK SYSTEM.

- **BENDING**
- A UNIQUE FEATURE ABOUT THIS SYSTEM IS THAT IT CAN BE CURVED AND BENT, AT A RADIUS OF JUST 20 CM. TO FACILITATE THIS, SPECIAL 90 DEGREE CORNER PIECES OF THE RECESS PROFILE ITSELF ARE AVAILABLE. CONTINUOUS CURVES UP TO A MINIMUM RADIUS OF 60 CM ARE ALSO POSSIBLE.
- IT IS ALSO POSSIBLE TO FIX THE VEROTEC- MTS® MEDICAL TRACK SYSTEM INTO THE RECESS PROFILE, THEREWITH CREATING A MANUAL RECESS CURTAIN TRACK.