

ARTICLE DATA SHEET



Article no.: 5.055
Product range: VEROFLEX
Material type: 100 % Polyester, plain weave
Weight: 340 gr/m²
Thickness: 0,38 mm
Widths: 89mm, 127mm, 2400mm, 3000mm



Maintenance instr. can be cleaned with a slightly humid towel (not washable)
Specifications:

- both side FR-coated (*inner side: white or colored / outer side: white*)
- darkening
- Flame-retardant properties tested and certified:
 - B1 acc. DIN 4102
 - French norm M1
 - Fire behavior class: B-s2,d0 acc. to DIN EN 13501-1
- Ecologically friendly acc. to OEKO-Tex Standard 100
no PVC
may contain traces of halogen due to the FR-coating
- Lightfastness acc. to DIN EN ISO 105 B02: 5 - 6
- restrictively suitable for humid areas
- **Antibacterial activity tested acc. to DIN EN ISO 20743:2013**
Fabric contains a Biocidal Product. Contains 4,5-Dichloro-2-octyl-2H-isothiazol-3-on by specific treatment to counter the settlement and growth of micro-organismsin/on the treated article.

COLOR	Visual optical figures			Solar optical figures			UV-Transm.	F _c -value [*]	Total energy transm. [*]
	interior			exterior					
	Rv	Tv	Av	Rs	Ts	As			
1	79%	0%	21%	66%	0%	34%	0%	0,50	36%
4	83%	0%	17%	71%	0%	29%	0%	0,46	33%
7	84%	0%	16%	72%	0%	28%	0%	0,46	33%
11	82%	0%	18%	71%	0%	29%	0%	0,47	34%
13	84%	0%	16%	72%	0%	28%	0%	0,46	33%
28	82%	0%	18%	69%	0%	31%	0%	0,48	34%
31	82%	0%	18%	69%	0%	31%	0%	0,48	34%
32	83%	0%	17%	71%	0%	29%	0%	0,46	33%
33	83%	0%	17%	71%	0%	29%	0%	0,47	34%
34	82%	0%	18%	70%	0%	30%	0%	0,47	34%
35	83%	0%	17%	71%	0%	29%	0%	0,46	33%
36	84%	0%	16%	71%	0%	29%	0%	0,48	34%
37	86%	0%	14%	73%	0%	27%	0%	0,47	33%
38	86%	0%	14%	73%	0%	27%	0%	0,47	33%
39	83%	0%	17%	71%	0%	29%	0%	0,48	34%
40	83%	0%	17%	71%	0%	29%	0%	0,48	33%
41	84%	0%	16%	71%	0%	29%	0%	0,48	33%
42	85%	0%	15%	73%	0%	27%	0%	0,47	33%
43	80%	0%	20%	68%	0%	32%	0%	0,50	35%
44	80%	0%	20%	69%	0%	31%	0%	0,49	35%
45	79%	0%	21%	66%	0%	34%	0%	0,51	36%
144	83%	0%	17%	70%	0%	30%	0%	0,49	34%
901	83%	0%	17%	71%	0%	29%	0%	0,46	33%

